

(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/078372 A1(51) International Patent Classification⁷: F28F 19/06,
19/02, 21/08, F25B 39/04

Oyama Regional Office, SHOWA DENKO K.K., 480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-8678 (JP). NAKAGAWA, Shintaro [JP/JP]; c/o Oyama Regional Office, SHOWA DENKO K.K., 480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-8678 (JP).

(21) International Application Number: PCT/JP2005/002533

(74) Agents: SHIMIZU, Hisayoshi et al.; Idemitsu Nagahori Building, 4-26, Minamisemba 3-chome, Chuo-ku, Osaka-shi, Osaka 542-0081 (JP).

(22) International Filing Date: 10 February 2005 (10.02.2005)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(26) Publication Language: English

(30) Priority Data:

2004-35356 12 February 2004 (12.02.2004) JP
60/545,529 19 February 2004 (19.02.2004) US


(71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MINAMI, Kazuhiko [JP/JP]; c/o Oyama Regional Office, SHOWA DENKO K.K., 480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-8678 (JP). TANAKA, Daishi [JP/JP]; c/o

[Continued on next page]

(54) Title: HEAT EXCHANGER AND METHOD FOR MANUFACTURING THE SAME



(57) **Abstract:** A method for manufacturing an aluminum heat exchanger includes the steps of: obtaining a heat exchanger tube 2 by forming a Zn thermally sprayed layer on a surface of an aluminum flat tube core so as to adjust Zn adhesion amount to 1 to 10 g/m²; obtaining a heat exchanger core by alternatively arranging the heat exchanger tube 2 and an aluminum fin 3 and brazing the heat exchanger tube and the fin with end portions of the heat exchanger tube connected to aluminum headers in fluid communication; and forming a chemical conversion treatment coat (corrosion resistance coat) on a surface of the heat exchanger core by subjecting the surface of the heat exchanger core to chemical conversion treatment using at least one chemical conversion treatment agent selected from the group consisting of phosphoric acid chromate, chromic acid chromate, phosphoric acid zirconium series, phosphoric acid titanium series, fluoridation zirconium series, and fluoridation titanium series. The obtained heat exchanger has a long last good corrosion resistance and can prevent occurrence of fin detachment and pit corrosion.

WO 2005/078372 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.